

Vinyl Fork Terminal For 16 - 14 AWG

By Burndy Catalog # TP1410F



Copper Terminal, Fork Tongue, 16-14 AWG, #8-#10 Stud, Vinyl Insulated, Tin Plated.

Features

- Fork terminals are constructed of pure electrolytic copper
- Long brazed seam barrel with deep V groove inner serations for optimum conductivity, reliability and holding power after crimping
- Fork tongue design for faster installation screw only needs to be loosened for termination
- Two or more terminals can be stacked on a common stud
- Provides maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Electro-tin plating for durable, long lasting corrosion resistance
- Inspection hole/skive provides an easy visual check of proper wire insertion
- 600 Volts maximum, 105°C maximum

Application

• For Commercial And Light Duty Industrial Control And Power Circuit Applications

General

Color Code	Blue
Connector Type	Fork Terminal
EU RoHS Indicator	Yes
Feature - Barrel Style	Shrouded
Insulation	Υ
Insulation Type	Vinyl
Material	Copper
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Fork
Plated	Υ
Plating Type	Tin
Sub Brand	VINYLUG
Trade Name	VINYLUG™
Туре	• TP-F
	• TP-F
UPC	781810712887
UPC 12 Digit	7818107128877

Dimensions

Cable Insulation Diameter Maximum	0.18 in
Dimension - B Length fraction	13/50 in
Dimension - B Length inch	0.26 in
Dimension - Bolt Size fraction	#10
Dimension - Hole Size fraction	1/5
Dimension - Hole Size inch	0.20 in
Dimension - L Length Overall mm	24 mm
Dimension - Length Overall inch	0.95 in
Dimension - Pad Width inch	0.41 in
Dimension - Strip Length inch	1/4 in
Dimension - Stud Size inch	#10
Dimension - Z (inch)	0.31 in

Electrical Ratings

Voltage -	Maximum	600
-----------	---------	-----

Conductor Related

Conductor Range	#16 AWG to #14 AWG
Conductor Size	16 - 14 AWG
Conductor Type	CU C Solid-Size
	CU C Str-Size

V

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	СМ
UL Listed	Yes

Logistics

Carton Quantity	1200
Minimum Pack Quantity	100
Pallet Quantity	99999

Product Assets

3D Models - TP1410F_MODEL-STEP 3D Models - TP1410F_MODEL-IGES

3D Models - TP1410F_MODEL-PDF Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Product Cross Section Image(s) - BUR_TP1010F_LineArt Sales Drawings - 50094171

HUBBELL

A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved. BRDY-TP1410F-SPEC-EN | REV 5/2024