

YA34A13, Aluminum Stackable **Terminal, Straight Lug**

By Burndy Catalog # YA34A13



Dimension - Strip Length inch 2-5/8 Physical Attribute - Tongue Straight Angle

Conductor Related

Conductor - AL Str Size 500 kcmil Conductor - AL Str Size Range 500 kcmil Conductor - Copper Str Size 500 kcmil

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	СМ
Status	
UL Listed	Yes

Logistics

Carton Quantity	12
Minimum Pack Quantity	1
Pallet Quantity	2880

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Installation Manuals - Aluminum Installation Instructions Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 210645 Specifications - YA34A13

General

Catalog Number	YA34A13
Color Code	Pink
Connector Type	Terminal
Die Index	300
Feature - Barrel Style	Chamfered
Material	Aluminum
Physical Attribute - Number of	2
Crimps Required	
Physical Attribute - Number of	2
Holes	
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
UPC	781810130728
UPC 12 Digit	7818101307288

Dimensions

Dimension - B Length inch	2.34 in
Dimension - Height fraction	49/50 in
Dimension - Height inch	0.98 in
Dimension - Hole Size fraction	5/9
Dimension - Hole Size inch	0.56 in
Dimension - L Length Overall	188 mm
mm	
Dimension - Length Overall	7.42 in
inch	
Dimension - Outside Diameter	1.32 in
inch	
Dimension - P inch	3.65 in
Dimension - Pad Width inch	1.62 in

©2025 Hubbell Incorporated. All rights reserved BRDY-YA34A13-SPEC-EN | REV 1/2025

