



# Uninsulated Ring Terminal For 3/0 AWG

By Burndy  
Catalog # [YAD27M20E34](#)



Uninsulated Ring Terminal For 3/0 AWG.

## Application

The YAD uninsulated OEM lug terminal is constructed of electrolytic copper

## General

Connector Type	Ring Terminal
EU RoHS Indicator	No
Feature - Barrel Type	Long
Material	Copper
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	TERMINALS, HYLUG
Trade Name	HYLUG™
Type	Ring Tongue
UPC	781810549513
UPC 12 Digit	7818105495133

## Dimensions

Dimension - B Length inch	0.79 in
Dimension - Bolt Size fraction	3/4
Dimension - Hole Size inch	0.80 in
Dimension - L Length Overall mm	58 mm
Dimension - Length Overall inch	2.37 in
Dimension - Outside Diameter inch	0.79 in
Dimension - Pad Width inch	1.14 in
Dimension - Strip Length inch	7/8
Dimension - Stud Size inch	3/4

## Electrical Ratings

Voltage - Maximum	600 V
-------------------	-------

## Conductor Related

Conductor - Copper Str Size	3/0 AWG
Conductor Size	3/0 AWG
Conductor Type	<ul style="list-style-type: none"><li>• CU C Str-Size</li><li>• CU C Flex-Size</li></ul>

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	250
Minimum Pack Quantity	25

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - 50013617](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
BRDY-YAD27M20E34-SPEC-EN | REV 8/2023