

Uninsulated Ring Terminal For 250 - 300 kcmil

By Burndy Catalog # YAD30M12E12



Uninsulated Ring Terminal For 250 - 300 kcmil.

Application

The YAD uninsulated OEM lug terminal is constructed of electrolytic copper

General

Connector Type	Ring Terminal
EU RoHS Indicator	No
Feature - Barrel Type	Long
Material	Copper
Physical Attribute - Tongue	Ring
Туре	
Plated	Y
Plating Type	Tin
Sub Brand	TERMINALS, HYLUG
Trade Name	HYLUG™
Туре	Ring Tongue
UPC	781810549599
UPC 12 Digit	7818105495999

Dimensions

Dimension - B Length inch	0.95 in
Dimension - Bolt Size fraction	1/2
Dimension - Hole Size inch	0.51 in
Dimension - L Length Overall mm	65 mm
Dimension - Length Overall inch	2.56 in
Dimension - Outside Diameter inch	1.00 in
Dimension - Pad Width inch	1.18 in
Dimension - Strip Length inch	1-1/8
Dimension - Stud Size inch	1/2

Electrical Ratings

Voltage - Maximum

Conductor Related

Conductor - Copper Str Size	250 kcmil;300 kcmil
Conductor - Copper Str Size Range	250 kcmil - 300 kcmil
Conductor Type	CU C Str-Size
	CU C Flex-Size

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	СМ
UL Listed	No

Logistics

Carton Quantity	100
Minimum Pack Quantity	10

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Product Cross Section Image(s) -BUR_YAD36M20E34_LineArt Sales Drawings - 50013664



600 V