

Uninsulated Ring Terminal For 8 AWG

By Burndy Catalog # YAD8CM10E38

Uninsulated Ring Terminal For 8 AWG.



Application

The YAD uninsulated OEM lug terminal is constructed of electrolytic copper

General

Connector Type Ring Terminal

EU RoHS Indicator No
Feature - Barrel Type Long
Material Copper
Physical Attribute - Tongue Ring
Type

Plated Y
Plating Type Tin

Sub Brand TERMINALS, HYLUG

 Trade Name
 HYLUG™

 Type
 Ring Tongue

 UPC
 781810548981

 UPC 12 Digit
 7818105489811

Dimensions

Dimension - B Length inch
Dimension - Bolt Size fraction
Dimension - Hole Size inch
Dimension - L Length Overall

30 mm

mm

Dimension - Length Overall 1.18 in

inch

Dimension - Outside Diameter 0.26 in

inch

Dimension - Pad Width inch 0.71 in Dimension - Strip Length inch 3/8 Dimension - Stud Size inch 3/8

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str Size 8 AWG
Conductor Size 8 AWG

Conductor Type • CU C Str-Size

• CU C Flex-Size

Certifications and Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467
Standards Met

Standards - RoHS Compliance NC

Status

UL Listed No

Logistics

Carton Quantity 2500 Minimum Pack Quantity 250

Product Assets

Customer Notices - Prop 65 Notice Sales Drawings - 50010577

