



YAEV2CL, Nylon Ring Terminal For 2 AWG

By Burndy
Catalog # [YAEV2CL](#)



Nylon Ring Terminal For 2 AWG.

Features

- Double thick tongue for maximum reliability and electrical capacity plus an extra strong terminal tongue
- Manufactured from one-piece pure electrolytic copper — high conductivity, low resistance with no seams to split plus ductility for excellent crimp forming properties
- Electro-tin plated to provide long-lasting corrosion resistance
- Nylon insulation is locked in place — Insulation will not move or twist off
- 600 volt nylon insulation providing high dielectric strength and stability in demanding oily environmental conditions
- Color Coded providing quick, easy wire size connector selection

Application

For Very Demanding High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants

General

Catalog Number	YAEV2CL
Color Code	Red
Connector Type	Ring Terminal
Die Index	438
EU RoHS Indicator	Yes
Insulation	Y
Insulation Type	Nylon
Material	Copper
Military Specification	MS25036
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin
Sub Brand	INSULUG
Trade Name	INSULUG™
Type	YAEV-L, Heavy Duty
UPC	781810027486
UPC 14 Digit GTIN	00781810027486

Dimensions

Dimension - B Length inch	0.57 in
---------------------------	---------

Dimension - Bolt Size fraction	3/8
Dimension - Length Overall inch	2.03 in
Dimension - N inch	0.34 in
Dimension - P inch	0.18 in
Dimension - Pad Width inch	0.69 in
Dimension - Stud Size inch	3/8
Dimension - Z (inch)	0.35 in

Electrical Ratings

Voltage - Maximum	600 V
-------------------	-------

Conductor Related

Conductor - Copper Str Aircraft Size	AN 2
Conductor - Copper Str Aircraft Size Range	AN 2
Conductor - Copper Str Size	2
Conductor Size	2 AWG
Conductor Type	<ul style="list-style-type: none">• CU C Solid-Size• CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	<ul style="list-style-type: none">• UL486• Military Specified (Mil-Spec)
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	200
Minimum Pack Quantity	200
Pallet Quantity	59200

Product Assets

[3D Models - YAEV2CL_MODEL-STEP](#)

[3D Models - YAEV2CL_MODEL-IGES](#)
[3D Models - YAEV2CL_MODEL-PDF](#)
[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)

[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_YAEV_LineArt](#)
[Sales Drawings - 50094163](#)
[Specifications - YAEV2CL](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
BRDY-YAEV2CL-SPEC-EN | REV 3/2025