

YAEV6CL, Nylon Ring Terminal For 6 AWG

By Burndy
Catalog # YAEV6CL

Copper Terminal, Ring Tongue w/ Inspection Hole, Wire Range 6 AWG, 1/4" Stud, Nylon Insulated, Short Barrel, Tin Plated, 600 Volts Max.



- Double thick tongue for maximum reliability and electrical capacity plus an extra strong terminal tongue
- Manufactured from one-piece pure electrolytic copper high conductivity, low resistance with no seams to split plus ductility for excellent crimp forming properties
- Electro-tin plated to provide long-lasting corrosion resistance
- Nylon insulation is locked in place Insulation will not move or twist off
- 600 volt nylon insulation providing high dielectric strength and stability in demanding oily evironmental conditions
- Color Coded providing quick, easy wire size connector selection

Application

For Very Demanding High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants

General

General	
Catalog Number	YAEV6CL
Color Code	Blue
Connector Type	Ring Terminal
Die Index	436
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Insulation	Υ
Insulation Type	Nylon
Material	Copper
Physical Attribute - Number of	1
Holes	
Physical Attribute - Tongue	Ring
Туре	
Plated	Υ
Plating Type	Tin
Sub Brand	INSULUG
Trade Name	INSULUG™
Туре	YAEV-L, Heavy Duty
UPC	781810027707
UPC 14 Digit GTIN	00781810027707



Dimensions

Dimension - B Length inch Dimension - Bolt Size fraction Dimension - Length Overall inch	0.42 in 1/4 1.56 in
Dimension - N inch Dimension - P inch	0.24 in 0.13 in
Dimension - Pad Width inch	0.48 in
Dimension - Stud Size inch	1/4
Dimension - Z (inch)	0.29 in

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str	AN 6
Aircraft Size	
Conductor - Copper Str	AN 6
Aircraft Size Range	
Conductor - Copper Str Size	6
Conductor Size	6 AWG
Conductor Type	 CU C Solid-Size
	 CU C Str-Size

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid
	till December 2024)
Certification - CSA Approved	No
Industry Standard(s)	• UL486
	 Military Specified (Mil-Spec)
Standards - Industry Standards	UL486
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes
Logistics	

Logistics

Carton Quantity	400
Minimum Pack Quantity	200
Pallet Quantity	800

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Terminals Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_YAEV_LineArt Sales Drawings - 50094163 Specifications - YAEV6CL



©2025 Hubbell Incorporated. All rights reserved BRDY-YAEV6CL-SPEC-EN | REV 3/2025