

YAK39A2G2, Aluminum -**Compression Stacking Terminal** (HYLUG Terminal)

By Burndy Catalog # YAK39A2G2

Al Stacking Terminal Lug, 750 kcmil(Al), 1.75" Spacing.



For Aluminum

General

Catalog Number YAK39A2G2 Connector Type Terminal Die Index 608;722;786

EU RoHS Indicator Yes Feature - Barrel Style Chamfered Material Aluminum Alloy

Physical Attribute - Number of

Crimps Required

Physical Attribute - Number of

Physical Attribute - Tongue Standard

Type

Plated

Plating Type Unplated

HYLUG, TERMINALS Sub Brand

Trade Name HYLUG™

Туре YAK-A-2G, Stacking Lug

8.22 in

UPC 781810187357 UPC 12 Digit 7818101873577

Dimensions

Dimension - B Length inch 2.65 in Dimension - Bolt Hole Size inch 0.50 in Dimension - D inch 3.06 in Dimension - Hole Size inch 0.56 in Dimension - L Length Overall 209 mm

mm

Dimension - Length Overall

inch

Dimension - N inch 0.62 in

Dimension - Outside Diameter 1.5 in



Dimension - Pad Width inch 1.62 in Dimension - Strip Length inch 2-3/4 in Physical Attribute - Tongue Straight

Angle

Conductor Related

Conductor - AL Str Size 750 kcmil Conductor - AL Str Size Range 750 kcmil Conductor - Copper Str Size 750 kcmil Conductor - Copper Str Size 750 kcmil

Range

Certifications And Compliance

Buy American Compliant Yes Certification - CSA Approved No Certification - ETL No Certification - UL Recognized No Certification - cULus Standards - RoHS Compliance CM Status

UL Listed No

Logistics

Minimum Pack Quantity 3

Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR_YAK-A-2G_LineArt

Sales Drawings - SD59493-01 Specifications - YAK39A2G2



