YAV0252M8, Compression Terminal

By Burndy
Catalog # YAV0252M8

HYLUG™ Copper tubing Compression terminals, 25 mm2, M8 Stud, 2 Holes, Tin Plated.

Features

- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damaging of the strands
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping
- Compatible Standards: IEC62138-1, UL 486A-468B, CSA-C22.2 No. 65-03

Application

Metric Wire Termination

General

Catalog Number	YAV0252M8
Connector Type	METRIC
Die Index	9
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Metric Terminals
UPC	781810637685
UPC 12 Digit	7818106376855

Dimensions

Dimension - B Length inch	0.27 in
Dimension - Bolt Size fraction	5/16
Dimension - Bolt Size inch	0.3125
Dimension - Hole Size fraction	5/16
Dimension - Hole Size inch	0.38
Dimension - Hole Size mm	10 mm
Dimension - L Length Overall mm	49.8 mm
Dimension - Length Overall inch	1.96 in
Dimension - Pad Width inch	11.0 in
Dimension - Strip Length inch	0.28 in
Dimension - Stud Size fraction	5/16
Dimension - Z (inch)	0.32 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Str Size	25 mm2
Conductor - Material	COPPER
Conductor Size	25 mm2
Conductor Type	CLASS 2

Certifications And Compliance

Certification - CSA Approved	No
Standards - RoHS Compliance Status	CM

Logistics

Minimum Pack Quantity	100

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Catalogs - BURNDY Master Catalog - Section C - Compression Connections
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_yavm_lineart
Sales Drawings - 50025887
Specifications - YAV0252M8

©2024 Hubbell Incorporated. All rights reserved