

Uninsulated Ring Terminal For 12 -10 AWG

By Burndy Catalog # YAV10HBOX

Seamless Copper Tube Uninsulated Ring Terminal, 12-10 AWG, 8-10, 1.05 in L, .38 in W.



Application

For Use On Copper Commercial (Code) Cable, Type AN Aircraft Cable And Extra Flexible Conductors

General

Connector Type Ring Terminal

EU RoHS Indicator Yes Feature - Barrel Style Shrouded Feature - Barrel Type Standard Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Tongue Ring

Type

Υ Plated Plating Type Tin Sub Brand **HYLUG** Trade Name HYLUG™ Type Ring Tongue UPC 781810532409

Dimensions

Cable Insulation Diameter 0.192 in Maximum Dimension - B Length fraction 5/16 in Dimension - B Length inch 0.31 in Dimension - Bolt Size fraction #8 - #10 Dimension - Hole Size fraction 1/5 Dimension - Hole Size inch 0.20 in Dimension - L Length Overall 27 mm mm Dimension - Length Overall 1.05 in inch Dimension - N inch 0.19 in Dimension - Outside Diameter 0.21 in inch Dimension - Pad Width inch 0.38 in Dimension - Strip Length inch 7/16 in Dimension - Stud Size inch #8:#10

Conductor Related

Conductor - Copper Str AN 12; AN 10

Aircraft Size

Conductor - Copper Str AN 12-AN 10

Aircraft Size Range

Conductor - Copper Str Navy 6 (7);6 (19);9 (7);9 (37)

Conductor - Copper Str Navy 6 (7)-9 (37)

Size Range

Conductor Range #12 AWG to #10 AWG

Conductor Size 12 - 10 AWG Conductor Type • CU C Solid-Size

• CU C Str-Size

Certifications And Compliance

Certification - CSA Approved Yes Certification - ETL Certification - UL Recognized Nο Certification - cULus No **UL467** Industry Standard(s) Standards - Industry **UL486** Standards Met

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

600 Carton Quantity Minimum Pack Quantity 50 Pallet Quantity 99999

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice

Product Cross Section Image(s) - BUR_YAV10H25BOX_LineArt

Sales Drawings - 50094162



Dimension - Z (inch)

0.28 in