



## YAV25M5, Compression Terminal

By Burndy

Catalog # [YAV25M5](#)

Copper Tubing Terminal, 1 Hole W/insp window, 25 mm Class  
2,5, 9 Index, 5 mm Stud.



## Application

Metric Wire Termination

## General

Catalog Number	YAV25M5
Connector Type	METRIC
Die Index	9
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Yes
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Metric Terminals
UPC	781810322550
UPC 12 Digit	7818103225500

## Dimensions

Dimension - B Length inch	0.50 in
Dimension - Bolt Size fraction	#8-#10
Dimension - Bolt Size inch	0.21
Dimension - Hole Size fraction	#10
Dimension - Hole Size inch	0.21
Dimension - Hole Size mm	5.3 mm
Dimension - L Length Overall mm	33.5 mm
Dimension - Length Overall inch	1.32 in
Dimension - N inch	0.25 in
Dimension - Outside Diameter inch	0.38 in
Dimension - Pad Width inch	0.55 in
Dimension - Strip Length inch	0.50 in
Dimension - Stud Size fraction	#10
Dimension - Z (inch)	0.27 in
Physical Attribute - Tongue Angle	Straight

## Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

## Conductor Related

Conductor - Material	COPPER
Conductor Size	25 mm <sup>2</sup>
Conductor Type	CLASS 2

## Certifications And Compliance

Certification - CSA Approved	Yes
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	50
Minimum Pack Quantity	50

## Product Assets

[3D Models - YAV25M5\\_MODEL-PDF](#)  
[3D Models - YAV25M5\\_MODEL-STEP](#)  
[3D Models - YAV25M5\\_MODEL-IGES](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Catalogs - BURNDY Master Catalog - Section C - Compression Connections](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_yavm\\_lineart](#)  
[Sales Drawings - 50025521](#)  
[Specifications - YAV25M5](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
BRDY-YAV25M5-SPEC-EN | REV 8/2024