

# Compression Terminal

By Burndy  
Catalog # [YAV50F2M10](#)

Cu Compression Lug, 2 Hole, W/Inspection Window, 50 mm, M10 Stud, 44.5 mm Spacing, Standard Barrel, 19 mm Wire Strip Length.



## Application

Metric Wire Termination

## General

Connector Type	METRIC
Die Index	12
Finish Type	Tin-Plated
Material	COPPER
Plated	Yes
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Metric Terminals
UPC	781810640654
UPC 12 Digit	7818106406544

## Dimensions

Dimension - B Length inch	0.69 in
Dimension - Bolt Hole Size inch	0.41 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - L Length Overall mm	94 mm
Dimension - Length Overall inch	3.70 in
Dimension - N inch	0.41 in
Dimension - Outside Diameter inch	0.56 in
Dimension - Pad Width inch	0.83 in
Dimension - Strip Length inch	0.69 in
Dimension - Stud Size fraction	3/8
Dimension - Z inch	0.42 in
Physical Attribute - Tongue Angle	Straight

## Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

## Conductor Related

Conductor - Material	COPPER
Conductor Size	50 mm <sup>2</sup>
Conductor Type	CLASS 2

## Certifications and Compliance

Certification - CSA Approved	No
Standards - RoHS Compliance Status	CM

## Logistics

Minimum Pack Quantity	20
-----------------------	----

## Product Assets

[3D Models - YAV50F2M10\\_MODEL-STEP](#)  
[3D Models - YAV50F2M10\\_MODEL-PDF](#)  
[3D Models - YAV50F2M10\\_MODEL-IGES](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Sales Drawings - 50025888](#)

