

Uninsulated Ring Terminal For 6 AWG

By Burndy Catalog # YAV6CL2BOX

Uninsulated Ring Terminal For 6 AWG.



Application

For Use On Type AN Aircraft Cable, Extra Flexible Conductors And Commercial (Code) Conductors, Industrials, Hospitals, Electric Utilities, Marine, Computers, And Other Equipment Subject To Vibration Or Requiring Dependable Electrical Performance

General

Connector Type Ring Terminal Die Index 39 **EU RoHS Indicator** Ves Feature - Barrel Style Chamfered Standard Feature - Barrel Type Material Copper Material Composition DLP Copper Tin Plating MS20659 Military Specification Physical Attribute - Number of 1 Holes Physical Attribute - Tongue Ring Туре Plated Plating Type Tin - Electro Plated HYI UG Sub Brand Trade Name HYLUG™ Туре Ring Tongue UPC 781810539156

Dimensions

Dimension - B Length fraction 1/2 in Dimension - B Length inch 0.50 in Dimension - Bolt Hole Size 0.39 in inch Dimension - Bolt Size fraction Dimension - Hole Size mm 10 mm Dimension - Length Overall 1.43 in inch Dimension - N inch 0.3 in Dimension - Outside Diameter 0.31 in inch Dimension - Pad Width inch 0.60 in Dimension - Strip Length inch 1/2 in Dimension - Stud Size inch 3/8 Dimension - Z inch 0.36 in Physical Attribute - Tongue Straight

Conductor Related

Conductor - Copper Str AN 6
Aircraft Size
Conductor - Copper Str Size 6
Conductor - Copper Str Size 6
AWG
Range
Conductor Size 6
CONDUCTOR SIZ

Certifications and Compliance

Certification - CSA Approved Yes Certification - ETL Nο Certification - UL Recognized Nο Certification - cULus Industry Standard(s) UL467 · Military Specified (Mil-Spec) Standards - Industry • UL467 Standards Met • Military Specified (Mil-Standards - RoHS Compliance

Standards - ROHS Compliance

Status

UL Listed Yes

Logistics

Carton Quantity 20 Minimum Pack Quantity 1

Product Assets

Catalogs - Full Line BURNDY Catalog Sales Drawings - 50094161_E Technical Solutions - BURNDY YAV6CL2BOX Specsheet



A proud member of the Hubbell Family.