

Compression Terminal

By Burndy
Catalog # [YAV95F2M8](#)

Cu Compression Metric Lug, 2 Hole, W/Inspection Window, 95 mm, M8 Stud, 44.5 mm Spacing, Standard Barrel, 27 mm Wire Strip Length.



Application

Metric Wire Termination

General

Connector Type	METRIC
Die Index	14
Finish Type	Tin-Plated
Material	COPPER
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Metric Terminals
UPC	781810640753
UPC 12 Digit	7818106407533

Dimensions

Dimension - B Length inch	1.00 in
Dimension - Bolt Size fraction	5/16
Dimension - Bolt Size inch	0.3125
Dimension - Hole Size fraction	5/16
Dimension - Hole Size inch	0.38
Dimension - Hole Size mm	10 mm
Dimension - L Length Overall mm	101 mm
Dimension - Length Overall inch	3.97 in
Dimension - N inch	0.34
Dimension - Pad Width inch	1.03 in
Dimension - Strip Length inch	1.06 in
Dimension - Stud Size fraction	5/16
Dimension - Z inch	0.36 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

Conductor Related

Conductor - Copper Str Size	2/0 AWG
Conductor - Material	COPPER
Conductor Size	95 mm ²
Conductor Type	CLASS 2

Certifications and Compliance

Certification - CSA Approved	No
Standards - RoHS Compliance Status	CM

Logistics

Minimum Pack Quantity	100
-----------------------	-----

Product Assets

[3D Models - YAV95F2M8_MODEL-IGES](#)
[3D Models - YAV95F2M8_MODEL-PDF](#)
[3D Models - YAV95F2M8_MODEL-STEP](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Sales Drawings - 50025888](#)