

YCA262NG6W, Copper compression terminal for terminating to switch pads, 2/0 Str, 2-hole, 1/2" Stud, 1-3/4" Spacing, Hot Tin Plated

By Burndy Catalog # YCA262NG6W

Cu Compression terminal Designed for terminating Cu Conductors to switch pads, 2/0 Str., 1/2 IN Stud, 2 Pad holes, Hot tin plated.



Catalog Number YCA262NG6W
Connector Type Terminal
Die Index K-5/8-1
Material Copper
Physical Attribute - Number of 2

Holes

Plated

Plating Type Tin - Hot Dipped

Prefilled Oxide Inhibitor N

Trade Name HYLUG™

UPC 781810088722

UPC 14 Digit GTIN 00781810088722

Dimensions

Dimension - B Length fraction
Dimension - B Length inch
Dimension - D inch
Dimension - Hole Size fraction
Dimension - Hole Size inch
Dimension - Hole Size mm
Dimension - Inside Diameter
Dimension - Inside Diameter
Dimension - B Length fraction
1.72 in
3.03 in
5/9
0.56 in
0.45 in

inch

Dimension - L Length Overall 135 mm

mm

Dimension - Length Overall 5.30 in

inch

Dimension - N inch 0.63 in Dimension - Outside Diameter 0.71 in

inch



Dimension - Pad Width inch

Dimension - Strip Length inch

Dimension - Z (inch)

Physical Attribute - Tongue

Angle

0.97 in

113/16

0.65 in

Straight

Conductor Related

Conductor - Copper Str Size 2/0 AWG Conductor - Copper Str Size 2/0 AWG Range

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	СМ
Status	

Logistics

UL Listed

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	5800

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - sd029071-012 Specifications - YCA262NG6W

No

