

YCA26RL2N, Al compression terminal, 2-Hole, 1/2" Stud, 1-3/4" Spacing, 2/0

By Burndy Catalog # YCA26RL2N

Aluminum compression lug designed for terminating overhead conductors to switch pads and other substation switch yard apparatus, Die index: 659.





Catalog Number YCA26RL2N Connector Type Terminal 659 Die Index Material Aluminum Physical Attribute - Pad 2 Hole NEMA

Configuration

Plated Ν

Plating Type Unplated

Prefilled Oxide Inhibitor Υ

Trade Name HYLUG™ UPC 781810810446 UPC 12 Digit 7818108104466

Dimensions

Dimension - B Length inch 2.70 in Dimension - Bolt Hole Size inch 0.5 in Dimension - E Spacing between 1-3/4 in

Holes fraction

Dimension - L Length Overall 168 mm

Dimension - Length Overall 6.62 in

0.83 in Dimension - Outside Diameter

inch

Dimension - Pad Width inch 1.12 in

Conductor Related

Conductor - ACSR Cmpt Size 2/0 AWG

Range



Conductor - ACSR Str Size 2/0 (6/1) Quail AWG Conductor - ACSR Str Size 2/0 (6/1) Quail AWG

Range

Conductor - AL Str Size 2/0 AWG Conductor - AL Str Size Range 2/0 AWG

Conductor Type ACSR C Str-Size

AAC

No

Certifications And Compliance

Certification - CSA Approved Nο Certification - ETL No No Certification - UL Recognized Certification - cULus No Standards - RoHS Compliance СМ Status

Logistics

UL Listed

Carton Quantity 25 Minimum Pack Quantity 25 Pallet Quantity 7400

Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_YCA_LineArt

Sales Drawings - SD052276-01 Specifications - YCA26RL2N

