

YCA26RL2N, Al compression terminal, 2-Hole, 1/2" Stud, 1-3/4" Spacing, 2/0

By Burndy
Catalog # [YCA26RL2N](#)



Aluminum compression lug designed for terminating overhead conductors to switch pads and other substation switch yard apparatus, Die index:659.

General

Catalog Number	YCA26RL2N
Connector Type	Terminal
Die Index	659
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Trade Name	HYLUG™
UPC	781810810446
UPC 12 Digit	7818108104466

Dimensions

Dimension - B Length inch	2.70 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	168 mm
Dimension - Length Overall inch	6.62 in
Dimension - Outside Diameter inch	0.83 in
Dimension - Pad Width inch	1.12 in

Conductor Related

Conductor - ACSR Cmppt Size Range	2/0 AWG
Conductor - ACSR Str Size	2/0 (6/1) Quail AWG
Conductor - ACSR Str Size Range	2/0 (6/1) Quail AWG
Conductor - AL Str Size	2/0 AWG
Conductor - AL Str Size Range	2/0 AWG
Conductor Type	<ul style="list-style-type: none"> • ACSR C Str-Size • AAC

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7400

Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_YCA_LineArt](#)
[Sales Drawings - SD052276-01](#)
[Specifications - YCA26RL2N](#)



A Hubbell brand