



# YCA30R2N, Al compression lug, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy  
Catalog # [YCA30R2N](#)



AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.71 IN L.

## Application

Aluminum compression HYLUGs for terminating overhead conductors to switch pads and substation or switch yard apparatus.

## General

Connector Type	Terminal
Construction Material - Main	Aluminum
Die Index	251
EU RoHS Indicator	Contact Manufacturer
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYLUG
Type	YCA-R-2N
UPC	781810810491
UPC 12 Digit	7818108104911

## Dimensions

Dimension - B Length inch	2.57 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	170 mm
Dimension - Length Overall inch	6.71 in
Dimension - Outside Diameter inch	1.00 in
Dimension - Pad Width inch	1.42 in

## Conductor Related

Conductor - ACSR Str Size	266.8 (18/1) Waxwing kcmil;266.8 (26/7) Owl kcmil;266.8 (26/7) Partridge kcmil
Conductor - ACSR Str Size Range	266.8 (18/1) Waxwing kcmil-266.8 (26/7) Partridge kcmil
Conductor - AL Str Size	266 kcmil
Conductor - AL Str Size Range	266 kcmil

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	20
Minimum Pack Quantity	1
Pallet Quantity	5920

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Product Cross Section Image\(s\) - BUR\\_YCA\\_LineArt](#)  
[Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-YCA30R2N-SPEC-EN | REV 5/2024