



## YCA321R2N

By Burndy  
Catalog # YCA321R2N

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.95 IN L.



### Application

Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.

### General

Connector Type	Terminal
Die Index	321
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL
Type	YCA-R-N
UPC	781810810736
UPC 12 Digit	7818108107366

### Dimensions

Dimension - B Length inch	2.68 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	178 mm
Dimension - Length Overall inch	7 in
Dimension - Outside Diameter inch	1.12 in
Dimension - Pad Width inch	1.54 in

### Conductor Related

Conductor - ACSR Str Size	336.4 (18/1) Merlin kcmil
Conductor - ACSR Str Size Range	336.4 (18/1) Merlin kcmil
Conductor - AL Str Size	336 kcmil
Conductor - AL Str Size Range	336.4 -350 Kcmil

### Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

### Logistics

Carton Quantity	20
Minimum Pack Quantity	1
Pallet Quantity	4800

### Product Assets

[Customer Notices - Prop 65 Notice](#)  
[Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.  
BRDY-YCA321R2N-SPEC-EN | REV 8/2023