



YCA33R2N, AL Compression Lug, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # [YCA33R2N](#)

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 7.29 IN L.



Application

Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.

General

Connector Type	Terminal
Die Index	316
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL
Type	YCA-R-N
UPC	781810016664
UPC 12 Digit	7818100166644

Dimensions

Dimension - B Length inch	3.00 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	185 mm
Dimension - Length Overall inch	7.29 in
Dimension - Outside Diameter inch	1.14 in
Dimension - Pad Width inch	1.60 in

Conductor Related

Conductor - AAAC 5005 Size	394.5 (19) kcmil
Conductor - AAAC 5005 Size Range	394.5 (19) kcmil
Conductor - AAAC 6201 Size	394.5 (19) kcmil
Conductor - AAAC 6201 Size Range	394.5 (19) kcmil
Conductor - ACSR Str Size	336.4 (26/7) Linnet kcmil; 336.4 (30/7) Oriole kcmil
Conductor - ACSR Str Size Range	336.4 (26/7) Linnet kcmil- 336.4 (30/7) Oriole kcmil
Conductor - AL Str Size	397.5 (19) Kcmil

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	10
Minimum Pack Quantity	1
Pallet Quantity	3920

Product Assets

[3D Models - YCA33R2N_MODEL-IGES](#)
[3D Models - YCA33R2N_MODEL-PDF](#)
[3D Models - YCA33R2N_MODEL-STEP](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_YCA_LineArt](#)
[Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-YCA33R2N-SPEC-EN | REV 5/2024

