

## YCA39R2N, Al Compression Lug, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy  
Catalog # [YCA39R2N](#)



AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 8.31 IN L.

### Application

Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.

### General

Catalog Number	YCA39R2N
Connector Type	Terminal
Die Index	608
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL
Trade Name	HYLUG™
Type	YCA-R-N
UPC	781810016688
UPC 12 Digit	7818100166888

### Dimensions

Dimension - B Length inch	3.59 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	211 mm
Dimension - Length Overall inch	8.31 in
Dimension - Pad Width inch	2.08 in

### Conductor Related

Conductor - ACSR Str Size	556.5 kcmil (24-7) ;556.5 kcmil (26-7)
Conductor - ACSR Str Size Range	556.5 (24-7) kcmil -556.5 (26-7) kcmil

### Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_YCA\\_LineArt](#)
- [Sales Drawings - SD..029515-01](#)
- [Specifications - YCA39R2N](#)