



# YCAK321R4N

By Burndy  
Catalog # [YCAK321R4N](#)



AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 7.09 IN L.

## Application

Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.

## General

Die Index	321
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	4 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL, TERMINAL
Trade Name	HYLUG™
Type	YCAK-R-N
UPC	781810810255
UPC 12 Digit	7818108102555

## Dimensions

Dimension - B Length inch	2.74 in
Dimension - Bolt Hole Size inch	0.56 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	180 mm
Dimension - Length Overall inch	7.09 in
Dimension - Pad Width inch	3 in

## Conductor Related

Conductor - ACSR Str Size	336.4 (18-1) kcmil
Conductor - ACSR Str Size Range	336.4 (18-1) kcmil
Conductor - AL Str Size	336.4 kcmil;350 kcmil
Conductor - AL Str Size Range	336.4 kcmil;350 kcmil

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

- [3D Models - YCAK321R4N\\_MODEL-STEP](#)
- [3D Models - YCAK321R4N\\_MODEL-IGES](#)
- [3D Models - YCAK321R4N\\_MODEL-PDF](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.