



YCAK37R4N, Al compression lug, 4-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # [YCAK37R4N](#)



AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 8.09 IN L.

Application

Used for terminating jumper loops and equipment taps at switchpads and other substation apparatus, or to YDW-R deadends.

General

Die Index	261
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	4 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	COMPRESSION TERMINAL
Type	YCAK-R-N
UPC	781810016763
UPC 12 Digit	7818100167633

Dimensions

Dimension - B Length inch	3.73 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - Hole Size inch	0.56 in
Dimension - L Length Overall mm	206 mm
Dimension - Length Overall inch	8.09 in
Dimension - Pad Width inch	3 in

Conductor Related

Conductor - ACSR Str Size Range	477 kcmil (24-7,26-7,30-7 STR),556.5 kcmil (18-1 STR)
Conductor - AL Str Size	556.5 kcmil (19 STR)

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

Product Assets

[3D Models - YCAK37R4N_MODEL-STEP](#)
[3D Models - YCAK37R4N_MODEL-IGES](#)
[3D Models - YCAK37R4N_MODEL-PDF](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Product Cross Section Image\(s\) - BUR_YCAK26R4N_LineArt](#)
[Sales Drawings - SD..029515-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-YCAK37R4N-SPEC-EN | REV 5/2024