

Compression C-Tap

By Burndy Catalog # YCHC29TC2

Copper Compression C Tap, 250 kcmil- 2 AWG (Main), 2-6 AWG (Tap 1), 8-14 AWG (Tap 2), Tin Plated.



Application

Wire Tap

General

Color Code Red
Connector Type C-TAP
Die Index 251
EU ROHS Indicator Yes

Finish Type Tin-Plated Material COPPER

Plated Y

Plating Type Tin - Electro Plated

Sub BrandCRIMPITTrade NameCRIMPIT™TypeYCHC SeriesUPC781810013755UPC 12 Digit7818100137555

Dimensions

Dimension - Height inch 1.78 in Dimension - L Length Overall 21 mm

mm

Dimension - Length Overall 0.81 in

inch

Dimension - Strip Length inch 1 in

Dimension - Width inch 0.97 in

Electrical Ratings

Voltage - Maximum 35000

Conductor Related

Conductor - Copper Flex I Run 2 AWG-4/0 AWG

Range

Conductor - Copper Flex K 2 AWG-4/0 AWG

Run Range

Conductor - Copper Flex M 2 AWG-4/0 AWG

Run Range

Conductor - Copper Solid Tap 6;5;4;3;2

Conductor - Copper Str Run 250 KCMIL-2 AWG Conductor - Copper Str Run 250 KCMIL-2 AWG

Range

Conductor - Copper Str Tap 2 AWG-6 AWG
Conductor - Copper Str Tap 2 AWG-6 AWG

Range

Conductor - Material COPPER

Conductor Size 250 KCMIL-2 AWG
Conductor Type CODE/FLEX

Certifications And Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) UL 486A-486B

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 60
Minimum Pack Quantity 1
Pallet Quantity 8880

Product Assets

Catalogs - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Sales Drawings - SD..206624-01

