

YDS32R, 2-piece, ACSR Splice, includes inner and outer sleeves

By Burndy Catalog # YDS32R

2-piece, full tension ACSR splice consists of steel inner sleeve and AL outer sleeve, Inner Sleeve: 6.88 IN L, Outer Sleeve: 22.25 IN L.

Features

- 2-Piece, Full Tension HYSPLICE consists of aluminum outer sleeve and steel inner sleeve
- Tapered out sleeve provides gradual transition of stress
- Filler hole provided for PENETROX Joint Compound
- Sizes 1/0 and larger come supplied with plugs for filler hole

YDS32R

Application

Catalog Number

For ACSR, Compressed And Compact Conductors

General

Connector Type	Splice
Die Index	252;316
Die Index - Element A	252
Die Index - Element B	316
EU RoHS Indicator	Yes
Material	Aluminum
Plated	Ν
Plating Type	Unplated
Prefilled Oxide Inhibitor	Υ
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS-R Set
UPC	781810821022
UPC 12 Digit	7818108210222

Dimensions

Dimension - Aluminum Sleeve	22.25 in
Length inch	
Dimension - L Length Overall	565 mm
mm	
Dimension - Length Overall	22.25 in
inch	
Dimension - Steel Sleeve	6.875 in
Length inch	



Conductor Related

Conductor - ACSR Cmpt Size	336.4 kcmil
Conductor - ACSR Cmpt Size	336.4 kcmil
Range	
Conductor - ACSR Str Size	336.4 (26/7) Linnet kcmil;336.4
	(30/7) Oriole kcmil
Conductor - ACSR Str Size	336.4 (26/7) Linnet kcmil-336.4
Range	(30/7) Oriole kcmil
Conductor Type	 ACSR C Str-Size
	 AL C Str-Size

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	СМ
Status	
UL Listed	No
Logistics	

Carton Quantity	10
Minimum Pack Quantity	1
Pallet Quantity	720

Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_YDS-R_LineArt Sales Drawings - SA..039024-01 Specifications - YDS32R

