


## YDS6W, Copper Full Tension Splice

By Burndy  
Catalog # [YDS6W](#)



HYSPLICE Single Sleeve Full Tension Splice, Accommodates Wire: #6 Cu Sol (Hard, Medium, or Soft Drawn), Die Index: 161, Made of copper tubing, Installed with standard tools and dies.

### Application

For Solid Copper Conductors

### General

Catalog Number	YDS6W
Connector Type	Splice
Die Index	161
EU RoHS Indicator	Yes
Material	Copper
Physical Attribute - Number of Crimps Required	4
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Sub Brand	HYSPLICE
Trade Name	HYSPLICE™
Type	YDS
UPC	781810820667

### Dimensions

Dimension - B Length inch	1.27 in
Dimension - L Length Overall mm	67 mm
Dimension - Length Overall inch	2.62 in
Dimension - Outside Diameter inch	0.32 in

### Conductor Related

Conductor - Copper Solid Size	6 AWG
-------------------------------	-------

### Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	RUS
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
UL Listed	No

### Logistics

Carton Quantity	100
Minimum Pack Quantity	1
Pallet Quantity	46400

### Product Assets

- [3D Models - YDS6W\\_MODEL-STEP](#)
- [3D Models - YDS6W\\_MODEL-IGES](#)
- [3D Models - YDS6W\\_MODEL-PDF](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR\\_YDS\\_LineArt](#)
- [Sales Drawings - SD..015142-02](#)
- [Specifications - YDS6W](#)