

YE32P250X125FX, Copper Compression Pin Adapter, 400 kcmil Cu

By Burndy Catalog # YE32P250X125FX

Type YE-P copper compression adapters are designed for reliable termination of copper conductor when the current capacity of the conductor is downsized, but larger conductor is utilized. Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used. Accommodates Copper Wire Sizes 400 KCMIL Class B & C, 300 KCMIL Classes G,H,I,K, 313 DLO



- Connector:Uninsulated copper compression pin adapter
- · Connection: Irreversible and maintenance free
- Long barrel lengths allow for an increased number of crimps, increasing the mechanical strength of the connection
- Material types include: Santoprene or PVC

Application

Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used

General

Color Code Blue
Connector Type INLINE PIN
Construction Material - Main Copper

EU RoHS Indicator Contact Manufacturer

Finish Type Tin-Plated
Material COPPER
Temperature Rating 90°C
Trade Name HYPLUG™
Type Connector
UPC 621945644748

Electrical Ratings

Voltage Rating 600 V



Conductor Related

Conductor - Copper DLO Size	313 KCMIL
Conductor - Copper Flex G Size	300 KCMIL
Conductor - Copper Flex G Size Range	300 KCMIL
Conductor - Copper Flex H Size	300 KCMIL
Conductor - Copper Flex I Size	300 KCMIL
Conductor - Copper Flex K Size	300 KCMIL
Conductor - Copper Str Compact Size	400 KCMIL
Conductor - Copper Str Size	400 KCMIL
Conductor - Material	COPPER
Conductor Size	400 KCMIL
Conductor Type	CODE/FLEX

Logistics

Carton Quantity 25
Pallet Quantity 3600

Product Assets

Catalog Page - BURNDY _CopperPinAdapter_CatCut Catalogs - Full Line BURNDY Catalog Sales Drawings - 50119221

