

YEV29P3/OX109FX, Copper Compression Pin Adapter, 250 kcmil Cu

By Burndy Catalog # YEV29P3/0X109FX

Type YE-P copper compression adapters are designed for reliable termination of copper conductor when the current capacity of the conductor is downsized, but larger conductor is utilized. Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used. Accommodates Copper Wire Sizes 250 KCMIL Class B & C, 4/O AWG Classes G,H,I,K,M, DLO



- Connector:Uninsulated copper compression pin adapter
- · Connection: Irreversible and maintenance free
- Long barrel lengths allow for an increased number of crimps, increasing the mechanical strength of the connection
- Material types include: Santoprene or PVC

Application

Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used

General

Color Code Yellow
Connector Type INLINE PIN
Construction Material - Main Copper
Die Index 16

EU RoHS Indicator Contact Manufacturer

Finish Type Tin-Plated
Material COPPER
Temperature Rating 90°C
Trade Name HYPLUG™
Type Connector
UPC 621945644724

Electrical Ratings

Voltage Rating 600 V



Conductor Related

Conductor - Copper DLO Size	4/0 AWG
Conductor - Copper Flex G Size	4/0 AWG
Conductor - Copper Flex H Size	4/0 AWG
Conductor - Copper Flex I Size	4/0 AWG
Conductor - Copper Flex K Size	4/0 AWG
Conductor - Copper Flex M Size	4/0 AWG
Conductor - Copper Str Compact Size	250 KCMIL
Conductor - Copper Str Size	250 KCMIL
Conductor - Material	COPPER
Conductor Size	250 KCMIL
Conductor Type	CODE/FLEX

Logistics

Carton Quantity 25
Pallet Quantity 6000

Product Assets

Catalog Page - BURNDY _CopperPinAdapter_CatCut Catalogs - Full Line BURNDY Catalog Sales Drawings - 50119221

