


# YFTW0614DL, Covered Twin Ferrule For 6 AWG

By Burndy Catalog # YFTW0614DL



## **Features**

- · Made of electrolytic copper, tin plated
- Smooth funnel entry to make wire insertion easier
- Secure contacting even after multiple reconnecctions
- Long-term contact resistance
- No fraying of strands
- No breakage of wire strands when wire is bent, under stress, or in vibration environment
- UL listed per UL486F requirements
- RoHS Compliant

## **Application**

For Use On Copper Conductor

#### General

Catalog Number YFTW0614DL
Connector Type End Termination

EU RoHS Indicator Yes
Insulation Y
Material Copper
Plated Y

Plating Type Tin - Electro Plated
Sub Brand FERRULES
Type Bootlace Ferrule
UPC 621945623149

# **Dimensions**

Dimension - D inch 0.35 in
Dimension - D1 inch 0.33 in

Dimension - D2 inch 0.72 in
Dimension - Length Overall 1.18 in
inch

# **Conductor Related**

Conductor - Copper Solid Size 6 AWG Conductor - Copper Str Size 6 AWG Conductor Size 6 AWG

# **Certifications And Compliance**

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - Industry Standards UL486

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

#### Logistics

Carton Quantity 100 Minimum Pack Quantity 100

#### **Product Assets**

Catalogs - BURNDY Master Catalog - Section B - Small Terminals Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50111876

Specifications - YFTW0614DL

