



# YHR750, Line Tap for Cu, AL, ACSR, Compact

By Burndy  
Catalog # YHR750



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, groove A(Run) ACSR:300 - 556 (18/1).

## Application

For Copper, Aluminum Or ACSR And Compact Conductors

## General

Die Index	KR
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Trade Name	HYCRIMP™
Type	YHR
UPC	781810139707

## Dimensions

Dimension - Height fraction	3-1/25 in
Dimension - Height inch	3.04 in
Dimension - L Length Overall mm	117 mm
Dimension - Length Overall inch	4.62 in
Dimension - Width fraction	1-37/50 in
Dimension - Width inch	1.74 in
Dimension - Width mm	44 mm

## Conductor Related

Conductor - ACSR Cmpt Run Range	397.5 (18/1) Chickadee kcmil;397.5 (24/7) Brant kcmil;397.5 (26/7) Ibis kcmil;397.5 (30/7) Larkspur kcmil;477.0 (18/1) Pelican kcmil;477.0 (24/7) Flicker kcmil;477.0 (26/7) Hawk kcmil;477. (30/7) Hen kcmil;500.0 (30/7) Heron kcmil;556.5 (24/7) Parakeet kcmil;636 kcmil
Conductor - ACSR Cmpt Tap	397.5 (18/1) Chickadee kcmil;397.5 (24/7) Brant kcmil;397.5 (26/7) Ibis kcmil;397.5 (30/7) Larkspur kcmil;477.0 (18/1) Pelican kcmil;477.0 (24/7) Flicker kcmil;477.0 (26/7) Hawk kcmil;477. (30/7) Hen

Conductor - ACSR Str Tap Range	300.0 (26/7) Ostrich kcmil-556.5 (18/1) kcmil
Conductor - AL Str Run	336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;600 kcmil
Conductor - AL Str Run Range	336 kcmil-600 kcmil
Conductor - AL Str Tap	300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;600 kcmil
Conductor - AL Str Tap Range	300 kcmil-600 kcmil
Conductor - Copper Str Run	350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil
Conductor - Copper Str Run Range	350 kcmil-600 kcmil
Conductor - Copper Str Tap	350 kcmil;400 kcmil;450 kcmil;500 kcmil;550 kcmil;600 kcmil
Conductor - Copper Str Tap Range	350 kcmil-600 kcmil

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	10
-----------------------	----

## Product Assets

- [3D Models - YHR750\\_MODEL-PDF](#)
- [3D Models - YHR750\\_MODEL-STEP](#)
- [3D Models - YHR750\\_MODEL-IGES](#)
- [Catalogs - Full Line BURNDY Catalog](#)

Conductor - ACSR Cmpt Tap Range	kcmil;500.0 (30/7) Heron kcmil;556.5 (24/7) Parakeet kcmil;636 kcmil
Conductor - ACSR Str Run	397.5 (18/1) Chickadee kcmil-636 kcmil
Conductor - ACSR Str Run Range	300.0 (26/7) Ostrich kcmil;336.4 (18/1) Merlin kcmil;336.4 (26/7) Linnet kcmil;336.4 (30/7) Oriole kcmil;397.5 (18/1) Chickadee kcmil;397.5 (24/7) Brant kcmil;397.5 (26/7) Ibis kcmil;397.5 (30/7) Larkspur kcmil;477.0 (18/1) Pelican kcmil;477.0 (24/7) Flicker kcmil;477.0 (26/7) Hawk kcmil;477. (30/7) Hen kcmil;500.0 (30/7) Heron kcmil;556.5 (18/1) kcmil
Conductor - ACSR Str Tap	300.0 (26/7) Ostrich kcmil-556.5 (18/1) kcmil
Conductor - ACSR Str Tap	300.0 (26/7) Ostrich kcmil;336.4 (18/1) Merlin kcmil;336.4 (26/7) Linnet kcmil;336.4 (30/7) Oriole



A proud member of the Hubbell Family.