



YHR950, Line Tap for Cu, AL, ACSR, Compact

By Burndy
Catalog # [YHR950](#)



Compression Line Tap for Copper, AL or ACSR and Compact Conductors, groove A(Run) ACSR:556.5 (18/1) - 954 (45/7).

Features

- Wide range, universal and reversible Figure H-Shaped aluminum connector
- Conductors are separated by the shape of the connector
- Bendable tabs secure both run and tap conductors freeing the installer to work with the installation tool
- Massive aluminum design miniizes corrosion due to galvanic corrosion
- Prefilled with PENETROX Joint Compound and individually packaged

Application

For Copper, Aluminum Or ACSR And Compact Conductors

General

Catalog Number	YHR950
Construction Material - Main	Aluminum
Die Index	KR
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYCRIMP
Trade Name	HYCRIMP™
Type	YHR
UPC	781810139905
UPC 14 Digit GTIN	00781810139905

Dimensions

Dimension - Height fraction	3-7/50 in
Dimension - Height inch	3.14 in
Dimension - Height mm	79.8 mm
Dimension - L Length Overall mm	152 mm
Dimension - Length Overall inch	6.00 in
Dimension - Width fraction	1-33/50 in
Dimension - Width inch	1.66 in
Dimension - Width mm	42 mm

Conductor Related

Conductor - ACSR Str Run

336.4 (24/7) Parakeet
kcmil;556.5 (26/7) Dove
kcmil;556.5 (30/7) Eagle
kcmil;605 (24/7) Peacock
kcmil;605 (26/7) Squab
kcmil;605 (30/19) Teal
kcmil;636 (24/7) Rook
kcmil;636 (26/7) Grosbeak
kcmil;636 (30/19) Egret
kcmil;666.6 (24/7) Flamingo
kcmil;715.5 (54/7) Crow
kcmil;715.5 (24/7) Stilt
kcmil;715.5 (26/7) Starling
kcmil;715.5 (30/19) Redwing
kcmil;795 (54/7) Condor
kcmil;795 (26/7) Drake
kcmil;795 (30/19) Mallard
kcmil;874.5 54/7 Condor
kcmil;900 (54/7) Canary
kcmil;954 (45/7) Rail kcmil

Conductor - ACSR Str Run Range

Conductor - ACSR Str Tap

336.4 (24/7) Parakeet kcmil-
954 (45/7) Rail kcmil
336.4 (18/1) Merlin kcmil;336.4
(26/7) Linnet kcmil;336.4
(30/7) Oriole kcmil;397.5 (18/1)
Chickadee kcmil;397.5 (24/7)
Brant kcmil;397.5 (26/7) Ibis
kcmil;397.5 (30/7) Larkspur
kcmil;477.0 (18/1) Pelican
kcmil;477.0 (24/7) Flicker
kcmil;477.0 (26/7) Hawk
kcmil;477. (30/7) Hen
kcmil;500.0 (30/7) Heron
kcmil;556.5 (24/7) Parakeet
kcmil;556.5 (26/7) Dove
kcmil;556.5 (30/7) Eagle
kcmil;605 (24/7) Peacock
kcmil;605 (26/7) Squab
kcmil;605 (30/19) Teal
kcmil;636 (24/7) Rook
kcmil;636 (26/7) Grosbeak
kcmil;636 (30/19) Egret
kcmil;666.6 (24/7) Flamingo
kcmil;715.5 (54/7) Crow
kcmil;715.5 (24/7) Stilt

Conductor - ACSR Str Tap Range	kcmil;715.5 (26/7) Starling	Conductor - Copper Str Run Range	350 kcmil-1000 kcmil
	kcmil;715.5 (30/19) Redwing	Conductor - Copper Str Tap	350 kcmil;400 kcmil;450
	kcmil;795 (54/7) Condor		kcmil;500 kcmil;550 kcmil;600
	kcmil;795 (26/7) Drake		kcmil;700 kcmil;750 kcmil;800
	kcmil;795 (30/19) Mallard		kcmil;850 kcmil;900 kcmil;1000
	kcmil;874.5 (54/7) Crane		kcmil
	kcmil;900 (54/7) Canary	Conductor - Copper Str Tap Range	350 kcmil-1000 kcmil
	kcmil;954 (45/7) Rail kcmil		
	336.4 (18/1) Merlin kcmil-954		
	(45/7) Rail kcmil		
Conductor - AL Str Run	336 kcmil;350 kcmil;397	Certifications And Compliance	
	kcmil;400 kcmil;450 kcmil;477	Certification - CSA Approved	No
	kcmil;500 kcmil;550 kcmil;556	Certification - ETL	No
	kcmil;600 kcmil;636 kcmil;650	Certification - UL Recognized	No
	kcmil;700 kcmil;715 kcmil;750	Certification - cULus	No
	kcmil;795 kcmil;800 kcmil;874	Standards - RoHS Compliance	CM
	kcmil;900 kcmil;954 kcmil;1000	Status	
	kcmil	UL Listed	No
	336 kcmil-1000 kcmil		
	336 kcmil;350 kcmil;397	Logistics	
Conductor - AL Str Run Range	kcmil;400 kcmil;450 kcmil;477	Minimum Pack Quantity	1
Conductor - AL Str Tap	kcmil;500 kcmil;550 kcmil;556	Product Assets	
	kcmil;600 kcmil;636 kcmil;650	3D Models - YHR950_MODEL-STEP	
	kcmil;700 kcmil;715 kcmil;750	3D Models - YHR950_MODEL-PDF	
	kcmil;795 kcmil;800 kcmil;874	3D Models - YHR950_MODEL-IGES	
	kcmil;900 kcmil;954 kcmil;1000	Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution	
	kcmil	Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog	
	336 kcmil-1000 kcmil	Interactive Catalog - BURNDY Full-Line Digital Catalog	
	350 kcmil;400 kcmil;450	Product Cross Section Image(s) - BUR_YH_LINEART	
	kcmil;500 kcmil;550 kcmil;600	Sales Drawings - SD..073376-01	
	kcmil;700 kcmil;750 kcmil;800	Specifications - YHR950	
Conductor - AL Str Tap Range	kcmil;850 kcmil;900 kcmil;1000		
Conductor - Copper Str Run	kcmil		