YKA28R2N, Disconnectable Terminal w/Fixed Hardware

By Burndy
Catalog # YKA28R2N

Disconnectable Terminal (With Fixed Hardware), 4/0 ACSR 4/0 (7, 19) Cu 4/0 (7, 19) Al, 6 in L.

Features

- Aluminum compression terminal with fixed hardware and positioning pin for making disconnectable tap or jumper connections
- Used with Slotted YTA-R-2N T-Tap or YSA-R-2N Terminal (sold separately)
- Supplied with aluminum bolts and washer
- Pre-filled with PENETROX Joint Compound and Capped

Application

For Copper, Aluminum, ACSR, 6201, 5005, Compressed And Compact Conductors And Making Disconnectable Tap Or Jumper Connections

General

Catalog Number	YKA28R2N
Connector Type	Terminal
Die Index	L;251
EU RoHS Indicator	Yes
Material	Aluminum
Physical Attribute - Pad Configuration	Straight
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	HYLUG
Type	YKA-R-2N, Disconnectable
UPC	781810820858

Dimensions

Dimension - B Length inch	1.97 in
Dimension - Bolt Size fraction	1/2
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	152 mm
Dimension - Length Overall inch	6 in
Dimension - Outside Diameter inch	1.06 in

Conductor Related

Conductor - ACSR Str Size	4/0 (6/1) Penquin AWG
Conductor - AL Str Size	4/0 AWG
Conductor - Copper Str Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1

Product Assets

3D Models - YKA28R2N_MODEL-STEP
3D Models - YKA28R2N_MODEL-PDF
3D Models - YKA28R2N_MODEL-IGES
Catalogs - BURNDY Master Catalog - Section H - Overhead Distribution
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_YKA342N_LineArt
Sales Drawings - SD051205
Specifications - YKA28R2N