

## YP27AU4, Figure 3-shaped Aluminum Connector with adjustable spacer

By Burndy  
Catalog # [YP27AU4](#)



Wide range, universal and reversible, Figure 3 shaped aluminum connector with adjustable overhanging spacer that separates conductors.

### Features

- Wide range universal and reversible, Figure 3-shaped aluminum connector features adjustable overhanging spacer that separates conductors
- Spacer holds run or tap in place, permitting lineman to either approach the line ready to crimp or to assemble connector and tap on run and then crimp
- Massive aluminum design minimizes conductor corrosion due to galvanic action
- Pre-filled with PENETROX joint compound and stripsealed

### Application

For Copper, Aluminum Or ACSR Conductors

### General

Catalog Number	YP27AU4
Die Index	D3
EU RoHS Indicator	Yes
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	CABELOK CRIMPIT
Trade Name	CABELOK™ CRIMPIT™
Type	YP-U
UPC	781810134481
UPC 12 Digit	7818101344811

### Dimensions

Dimension - Height inch	1.70 in
Dimension - Length Overall inch	1.69 in
Dimension - Width inch	0.97 in

### Conductor Related

Conductor - ACSR Str Size A Range	1/0 (6/1) Raven AWG;2/0 (6/1) Quail AWG
Conductor - ACSR Str Size A Range	1/0 (6/1) Raven AWG-2/0 (6/1) Quail AWG

Conductor - ACSR Str Size B Range	6 (6/1) Turkey AWG;5 (6/1) Thrush AWG;4 (6/1) Swan AWG;4 (7/1) Swanate AWG
Conductor - AL Str Size A Range	6 (6/1) Turkey AWG-4 (7/1) Swanate AWG
Conductor - AL Str Size A Range	1/0 AWG;2/0 AWG
Conductor - AL Str Size B Range	1/0 AWG-2/0 AWG
Conductor - AL Str Size B Range	6 AWG;4 AWG
Conductor - AL Str Size B Range	6 AWG-4 AWG
Conductor - Copper Solid Size A Range	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size A Range	2/0 AWG-4/0 AWG
Conductor - Copper Solid Size B Range	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Solid Size B Range	2/0 AWG-4/0 AWG
Conductor - Copper Str Size A Range	1/0 ;2/0 AWG;3/0 AWG
Conductor - Copper Str Size A Range	1/0 -3/0 AWG
Conductor - Copper Str Size B Range	6 AWG;5 AWG;4 AWG;3 AWG
Conductor - Copper Str Size B Range	6 AWG-3 AWG

### Certifications And Compliance

Buy American Compliant	No
Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

### Logistics

Minimum Pack Quantity	1
-----------------------	---

### Product Assets

Catalogs - BURNDY Master Catalog - Section H - Overhead  
Distribution  
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog  
Interactive Catalog - BURNDY Full-Line Digital Catalog

Product Cross Section Image(s) - BUR\_YPU\_Lineart  
Sales Drawings - sd045569-01  
Specifications - YP27AU4



A Hubbell brand