

YRB2U6, Compression Splice Reducer, Barrel A 2/0 AWG, Barrel B #6 AWG, AL9CU

By Burndy Catalog # YRB2U6

Splice reducer is rated to accommodate both alumium and copper wire, barrel is designed with an internal chamfer for smooth wire insertion, tin plated for corrosion resistance, prefilled PENETROX™ A13 oxide inhibitor, comes with color coded end caps, UL 486A-486B, CSA, rated up to 90°C and 35kV.



Application

Wire Reducing Splice

General

Catalog Number YRB2U6
Color Code Tan
Connector Type DUAL RATED

Die Index 296

Die Index 296

Feature - Barrel Style Chamfered
Finish Type Tin-Plated
Material ALUMINUM

Plated Y

Plating Type Tin - Electro Plated

Temperature Rating 194

 Trade Name
 HYREDUCER™

 UPC
 781810088524

 UPC 12 Digit
 7818100885244

Dimensions

Dimension - B Length fraction 7/8 in
Dimension - B Length inch 0.88 in
Dimension - L Length Overall 51 mm

mm

Dimension - Length Overall 2.00 in

inch

Dimension - Outside Diameter 0.65 in

inch

Dimension - Strip Length inch 15/16

Electrical Ratings

Voltage - Maximum 35000

Conductor Related

2 AWG Conductor - AL Str Run Conductor - AL Str Size A 2:1 Conductor - AL Str Size A 2-1 Range Conductor - AL Str Size B 6 Conductor - AL Str Size B Conductor - AL Str Tap 6 AWG 2 AWG Conductor - Copper Str Run Conductor - Copper Str Size 2:1 Conductor - Copper Str Size B Conductor - Copper Str Size B 6-5 Range

Conductor - Copper Str Tap 6 AWG

Conductor - Material ALUMINUM / COPPER

Conductor Type CODE

Certifications And Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Met

Standards - RoHS Compliance CM

Status


UL Listed Yes

Logistics

Carton Quantity 25
Minimum Pack Quantity 100
Pallet Quantity 11600

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Sales Drawings - 50123311 Specifications - YRB2U6



©2024 Hubbell Incorporated. All rights reserved BRDY-YRB2U6-SPEC-EN | REV 8/2024