YSM8C, Uninsulated Parallel Splice For 6,088 - 16,864 cmils

By Burndy
Catalog # YSM8C

Uninsulated Parallel Splice For 6,088 - 16,864 cmils.

Features

- Seamless tubing
- Beveled barrel for ease of wire entry
- Tin plated
- Parallel design results in only one crimp necessary
- Uninsulated barrel provides an economical termination solution when insulation is not specified

Application

HYLINK Type YSM seamless parallel splice connector permits wires to be laid parallel inside the connector and spliced together with the BURNDY family of HYTOOL installation tooling

General

Catalog Number	YSM8C
Connector Type	Parallel Splice
EU RoHS Indicator	Yes
Feature - Barrel Style	Chamfered
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYLINK
Temperature Rating	90
Trade Name	HYLINK™
Type	YSM
UPC	781810805794
UPC 12 Digit	7818108057944

Dimensions

Dimension - Length Overall inch	0.41 in
Dimension - Outside Diameter inch	0.27 in
Dimension - Strip Length inch	1/2

Conductor Related

Conductor - Copper Str Size	12 AWG;10 AWG;9 AWG;8 AWG
Conductor - Copper Str Size Range	12 AWG-8 AWG
Conductor Size	6,088 - 16,864 cmils
Conductor Type	• CU C Solid-Size • CU C Str-Size

Certifications And Compliance

Buy American Compliant	Yes
Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Carton Quantity	200
Minimum Pack Quantity	200

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Compression
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Interactive Catalog - BURNDY Full-Line Digital Catalog
Sales Drawings - 50094200
Specifications - YSM8C

©2024 Hubbell Incorporated. All rights reserved