

AGSKIT250, Splice Kit, 1 AWG-250 kcmil, Heavy Wall Heat Shrink Sleeve, Al/Cu Rated

By Burndy Catalog # AGSKIT250

Splice Kit, 1 AWG-250 kcmil, w/ Heavy Wall Heat Shrink Sleeve, Al/Cu Rated.



Features

- Dual Rated Aluminum or Copper/Aluminum Combinations
- Installed with common installation tools
- Heavy wall heat shrink sleeve is lined with adhesive material providing a positive seal against moisture egress

General

Application For All Aluminum or
Copper/Aluminum
Combinations
Catalog Number AGSKIT250
Connector Type Splice/Heat Shrink Kit
EU RoHS Indicator Contact Manufacturer

Hex Size 5/16
Insulation Y
Material Aluminum
Material - Hardware Aluminum

Physical Attribute - Screw Type Allen
Plated N
Plating Type Unplated
Sub Brand SPLICE KIT
Temperature Rating 194° F

Type AGSKIT, Above Grade

UPC 781810175262 UPC 12 Digit 7818101752622

Dimensions

Dimension - L Length Overall 127 mm

mm

Dimension - Length Overall 5 in

inch

Electrical Ratings

Rating - Minimum Voltage 600

Conductor Related

Conductor - AL Str Size 1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil Conductor - AL Str Size Range 1 AWG-250 kcmil Conductor - Copper Solid Size 1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG Conductor - Copper Solid Size 1 AWG-4/0 AWG Range 1 AWG;1/0 ;2/0 AWG;3/0 Conductor - Copper Str Size AWG;4/0 AWG;250 kcmil Conductor - Copper Str Size 1 AWG-250 kcmil Range 1 AWG-250 KCMIL Conductor Size Conductor Type AL C Str-Size CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct	No
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Product Assets

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section A - Mechanical Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_AGSKIT_LineArt Sales Drawings - SD..211383-01

