

BIBS75012, Single Sided Twelve Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BIBS75012



MULTI-PORT Single-Sided Entry.

Features

- Clear Plastisol covered AL6061-T6 aluminum body saves times and lowers installation costs and eliminates taping
- Clear plastisol allows visual confirmation that conductor is properly inserted
- Oxide inhibitor pre-installed inhibits moisture and contaminants from entering the contact area
- Range-taking capability reduces number of connectors necessary to carry in inventory

General

Catalog Number	BIBS75012
Connector Type	Multi Tap
Hex Key	3/8
Insulation	Υ
Insulation Type	Plastisol
Material	Aluminum
Number Of Ports	12
Physical Attribute - Number of	12
Screws	
Physical Attribute - Screw Type	Allen
Plated	Ν
Plating Type	Unplated
Temperature Rating	194
Trade Name	UNITAP™
UPC	781810233115
UPC 12 Digit	7818102331155

Dimensions

Dimension - Height inch	3.00 in
Dimension - L Length Overall	416 mm
mm	
Dimension - Length Overall	16.38 in
inch	
Dimension - Width inch	2.70 in
Dimension - Width mm	69 mm

Electrical Ratings

Operating Voltage	600 V
Voltage - Maximum	600 V

Conductor Related

Conductor - AL Str Size Range	2 - 750 Str
Conductor - Copper Str Size	2 - 750 Str
Range	
Conductor Size	2 AWG-750 KCMIL
Conductor Type	AL C Str-Size
	CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	No
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	
Standards - RoHS Compliance	СМ
Status	
UL Listed	No

Product Assets

Catalogs - UNITAP[™] Products Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Catalogs - BURNDY Master Catalog - Section A - Mechanical Customer Notices - Prop 65 Notice Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_BIBS_Lineart Sales Drawings - sc210991-15



©2024 Hubbell Incorporated. All rights reserved BRDY_CA-BIBS75012-SPEC-EN | REV 6/2024