



## K2C22, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy

Catalog # [K2C22](#)



Mechanical Grounding Connector, 2 Cables to Flat, 10 - 3 AWG (Str) / 10 - 2 AWG (Sol), 3/8" Stud.

### Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

### Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

### General

|                                      |                      |
|--------------------------------------|----------------------|
| Catalog Number                       | K2C22                |
| EU RoHS Indicator                    | Yes                  |
| Material                             | Bronze Alloy, Leaded |
| Plated                               | N                    |
| Plating Type                         | Unplated             |
| Stud Installation Torque inch pounds | 280 LBS/in           |
| Sub Brand                            | SERVIT POST          |
| Trade Name                           | SERVIT POST™         |
| Type                                 | KC and K2C Series    |
| UPC                                  | 781810257104         |
| UPC 14 Digit GTIN                    | 00781810257104       |

### Dimensions

|                                 |          |
|---------------------------------|----------|
| Dimension - B Length fraction   | 15/32 in |
| Dimension - B Length inch       | 0.46 in  |
| Dimension - Body Width inch     | 0.62 in  |
| Dimension - Bolt Size fraction  | 3/8      |
| Dimension - D inch              | 0.62 in  |
| Dimension - Height fraction     | 1        |
| Dimension - Height inch         | 1.25 in  |
| Dimension - Height mm           | 25.4 mm  |
| Dimension - L Length Overall mm | 41.1 mm  |
| Dimension - Length Overall inch | 1.62 in  |
| Dimension - Nut Width inch      | 0.75 in  |
| Dimension - P inch              | 0.26 in  |
| Dimension - Threads per inch    | 16       |
| Dimension - Width inch          | 32 mm    |

### Conductor Related

|  |  |
|--|--|
| Conductor - Copper Solid Size                                | 10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG |
| Conductor - Copper Solid Size Range                          | 2 AWG - 10 AWG   |
| Conductor - Copper Str Size                                  | 10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG       |
| Conductor - Copper Str Size Range                            | 3 AWG - 10 AWG   |
| Physical Attribute - Number of Conductors Accommodated Total | 2  |

### Certifications And Compliance

|   |       |
|---|-------|
| Certification - CSA Approved            | No    |
| Certification - ETL                     | No    |
| Certification - UL Listed Direct Burial | Yes   |
| Certification - UL Recognized           | No    |
| Certification - cULus                   | No    |
| Industry Standard(s)                    | UL467 |
| Standards - Industry Standards Met      | UL467 |
| Standards - RoHS Compliance Status      | EX    |
| UL Listed                               | Yes   |

### Logistics


|                 |       |
|-----------------|-------|
| Carton Quantity | 50    |
| Pallet Quantity | 14850 |

### Product Assets

[3D Models - K2C22\\_MODEL-PDF](#)  
[3D Models - K2C22\\_MODEL-IGES](#)  
[3D Models - K2C22\\_MODEL-STEP](#)  
[Catalogs - Burndy Grounding Catalog](#)  
[Catalogs - BURNDY Master Catalog - Section E2 - Mechanical Grounding](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)

Product Cross Section Image(s) - BUR\_K2C\_Lineart  
Sales Drawings - SD..055917

Specifications - K2C22 Specification Sheet English  
Specifications - K2C22 Specification Sheet French



©2025 Hubbell Incorporated. All rights reserved  
BRDY\_CA-K2C22-SPEC-EN | REV 4/2025