

K2C28, SERVIT POST Mechanical Connector, 2 Cables to Flat

By Burndy Catalog # K2C28

Mechanical Grounding Connector, Cable to Flat, 1-4/0 AWG, Stud Dia:5/8-11.



Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

General

Catalog Number K2C28 **EU RoHS Indicator** Yes

Material Copper Alloy

Plated

Plating Type Unplated Stud Installation Torque inch 660 LBS/in

pounds

Sub Brand SERVIT POST SERVIT POST™ Trade Name KC and K2C Series Type UPC 781810257500 UPC 12 Digit 7818102575000

Dimensions

Dimension - B Length fraction 3/4 in Dimension - B Length inch 0.75 in Dimension - Body Width inch 1.18 in Dimension - Bolt Size fraction 5/8 Dimension - D inch 1.00 in Dimension - Height fraction 1-3/4 Dimension - Height inch 2.46 in Dimension - L Length Overall 88 m mm Dimension - Length Overall 3.45 in inch Dimension - Nut Width inch 1.35 in Dimension - P inch 0.55 in Dimension - Threads per inch Dimension - Width inch 62 mm

Conductor Related

Conductor - Copper Solid Size 1 AWG;1/0 AWG;2/0 AWG;3/0

AWG;4/0 AWG

Conductor - Copper Solid Size 1 AWG-4/0 AWG

Conductor - Copper Str Size 1 AWG;1/0 ;2/0 AWG;3/0

AWG;4/0 AWG 4/0 AWG-1 AWG

Conductor - Copper Str Size

Physical Attribute - Number of 2 Conductors Accommodated

Certifications And Compliance

Certification - CSA Approved Certification - ETL Nο Certification - UL Listed Direct Yes

Burial

Certification - UL Recognized Certification - cULus Nο Industry Standard(s) **UL467** Standards - Industry UL467

Standards Met

Standards - RoHS Compliance

Status

UL Listed Yes

Product Assets

3D Models - K2C28 MODEL-STEP

3D Models - K2C28_MODEL-PDF

3D Models - K2C28_MODEL-IGES Catalogs - Full Line BURNDY Catalog

Catalogs - Section E2 - Mechanical Grounding

Customer Notices - Prop 65 Notice

Product Cross Section Image(s) - BUR K2C Lineart

Sales Drawings - SD..055917

