

Nylon Ring Terminal For 16 - 14 AWG

By Burndy Catalog Number YAEV14

CU Ring Tongue Terminal, 1 Hole/W/InspWindow, #20-#14 AWG, 600 V, #8-#10 Stud, Nylon Insulated, Seamless Barrel, Tin Plated



General

Application For High Vibration

Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating

Plants

Color Code Blue

Connector Type Ring Terminal

EU RoHS Indicator Yes
Insulation Y
Insulation Type Nylon
Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Tongue Ring

Type

Plated Y
Plating Type Tin
Sub Brand INSULUG
Trade Name INSULUG™

Type YAEV, Heavy Duty
UPC 781810027783
UPC 12 Digit 7818100277833

Dimensions

Dimension - Bolt Size fraction #8 - #10
Dimension - Hole Size fraction 1/5
Dimension - Hole Size inch 0.20 in
Dimension - N inch 0.16 in
Dimension - Pad Width inch 0.31 in
Dimension - Stud Size inch #8;#10
Dimension - Width inch 0.10 in
Dimension - Z inch 0.24 in

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str AN 18;AN 16;AN 14

Aircraft Size

Conductor - Copper Str AN 18-AN 14

Aircraft Size Range

Conductor - Copper Str Size 18;16;14

Conductor - Copper Str Size 18 AWG - 14 AWG

Range

Conductor Size 16 - 14 AWG

Conductor Type • CU C Solid-Size

• CU C Str-Size

Certifications and Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) • UL486

Military Specified (Mil-

Spec)

Standards - Industry • UL486

Standards Met

• Military Specified (Mil-

Spec)

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 1000 Pallet Quantity 99000

Product Assets

3D Models - YAEV14_MODEL-PDF 3D Models - YAEV14_MODEL-STEP 3D Models - YAEV14_MODEL-IGES

Sales Drawings - 50094163

Technical Solutions - BURNDY_YAEV14_Specsheet

