

Nylon Ring Terminal For 16 - 14 **AWG**

By Burndy Catalog # YAEV14BOX

Ring Tongue Copper Tubing Terminal, .94 in L, .31 in W, Tin Plated, 600 Volts Max., 105 Deg C Max.



Application

For High Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And Generating Plants

General

Catalog Number YAEV14BOX Color Code Blue

Connector Type Ring Terminal

EU RoHS Indicator Yes Insulation Nylon Insulation Type Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Tongue Ring

Туре

Plated Υ Plating Type Tin Sub Brand **INSULUG** Temperature Rating 105°C INSULUG™ Trade Name

Type YAEV, Heavy Duty UPC 781810023327 UPC 12 Digit 7818100233277

Dimensions

Dimension - Bolt Size fraction #8 - #10 Dimension - Hole Size fraction 1/5 Dimension - Hole Size inch 0.20 in Dimension - L Length Overall 24 mm mm 0.94 in

Dimension - Length Overall

inch

Dimension - N inch 0.16 in Dimension - Pad Width inch 0.31 in Dimension - Strip Length inch Dimension - Stud Size inch #8:#10 Dimension - Z (inch) 0.24 in

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str AN 18; AN 16; AN 14

Aircraft Size

Conductor - Copper Str

Aircraft Size Range

Conductor - Copper Str Size Conductor - Copper Str Size

Range

Conductor Size

Conductor Type

AN 18-AN 14

18 AWG:16 AWG:14 AWG

18 AWG - 14 AWG

16 - 14 AWG

• CU C Str Aircraft-Size

• CU C Str-Size

Certifications And Compliance

Certification - CSA Approved Nο Certification - ETL Certification - UL Recognized No Certification - cULus

 UL486 Industry Standard(s)

· Military Specified (Mil-

Spec)

Standards - Industry UL486; Military Specified (Mil-

Standards Met Spec)

Standards - RoHS Compliance

Status

UL Listed Yes

Logistics

Carton Quantity 100

Product Assets

Catalogs - Full Line BURNDY Catalog Catalogs - Section B - Small Compression

Product Cross Section Image(s) - BUR_YAEV10BOX_LineArt

Sales Drawings - 50094163