

Nylon Ring Terminal For 2 AWG

By Burndy Catalog Number YAEV2CH

Ring-Tongue Terminals, 2 Max. Insul.Dia.: .52", Sleeve,Color: Red, 3/8, 2.34 in L, Nylon-Insulated For Expanded Insulation, 600 Volts Max.



General

Application For Very Demanding High

Vibration Applications Encountered In Aircraft And Aboard Ships As Well As Motor Lead Applications In Hospitals, Industrials And

Generating Plants

Color Code Rec

Connector Type Ring Terminal

Die Index 438
EU RoHS Indicator Yes
Feature - Barrel Style Belled
Feature - Barrel Type Standard

Insulation Y
Insulation Type Nylon
Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Tongue Ring

Type

Plated Y Plating Type Tin

Sub Brand TERMINALS, INSULUG

 Trade Name
 INSULUG™

 Type
 YAEV-H

 UPC
 781810027479

 UPC 12 Digit
 7818100274799

Dimensions

Dimension - B Length inch 0.57 in
Dimension - Bolt Hole Size 0.39 in

inch

Dimension - Bolt Size fraction 3/8
Dimension - D inch 0.69 in
Dimension - Length Overall 2.33 in

inch

Angle

Dimension - N inch

Dimension - Pad Width inch

Dimension - Strip Length inch

Dimension - Stud Size inch

Dimension - Z inch

Physical Attribute - Tongue

0.34 in
0.69 in
5/8
3/8
0.35 in
Straight

Electrical Ratings

Voltage - Maximum 600 V

Conductor Related

Conductor - Copper Str

Aircraft Size

Conductor - Copper Str Size 2

Conductor Size 2 AWG

Conductor Type • CU C Solid-Size

• CU C Str-Size

AN 2

Certifications and Compliance

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Industry Standard(s) • UL486

 Military Specified (Mil-Spec)

Standards - Industry Standards Met • UL486

Military Specified (Mil-

Spec)

Standards - RoHS Compliance

Status

UL Listed Yes

Product Assets

3D Models - YAEV2CH_MODEL-STEP 3D Models - YAEV2CH_MODEL-IGES 3D Models - YAEV2CH_MODEL-PDF

Sales Drawings - 50094164

Technical Solutions - BURNDY_YAEV2CH_Specsheet

