

Uninsulated Ring Terminal For 12 -10 AWG

By Burndy Catalog Number YAV10H3

Copper Compression Lug, Heavy Duty, Ring Tongue with Shroud, 1 Hole w/ Inspection Hole, 12-10 AWG, 1/4" Stud, Short Barrel, Tin Plated.



General

Application For Use On Copper Commercial (Code) Cable, Type AN Aircraft Cable And Extra Flexible Conductors Ring Terminal Connector Type **EU RoHS Indicator** Yes Feature - Barrel Style Shrouded Material Copper Physical Attribute - Tongue Ring Type Plated

5/16 in

Tin - Electro Plated Plating Type Sub Brand **HYLUG** Trade Name HYLUG™ Type Ring Tongue UPC 781810024928

Dimensions

Dimension - B Length fraction Dimension - B Length inch 0.31 in Dimension - Bolt Size fraction 1/4 Dimension - Hole Size inch 0.27 in Dimension - L Length Overall 30 mm Dimension - Length Overall 1.17 in inch Dimension - N inch 0.23 in Dimension - Outside Diameter 0.21 in Dimension - Pad Width inch 0.47 in Dimension - Strip Length inch 7/16 in Dimension - Stud Size inch 1/4 in Dimension - Z inch 0.36 in

Conductor Related

Conductor - Copper Str Size 12 AWG;10 AWG Conductor - Copper Str Size 12 AWG-10 AWG Range 12 - 10 AWG Conductor Size • CU C Solid-Size Conductor Type • CU C Str-Size

Certifications and Compliance

Certification - CSA Approved Certification - ETL No Certification - UL Recognized Certification - cULus Nο Industry Standard(s) **UL467** Standards - Industry **UL467** Standards Met Standards - RoHS Compliance Status

UL Listed Logistics

1000 Carton Quantity Pallet Quantity 99999

Product Assets

Customer Notices - Prop 65 Notice Sales Drawings - 50094162 Technical Solutions - BURNDY_YAV10H3_Specsheet

Yes

