

Uninsulated Ring Terminal For 16 - 14 AWG

By Burndy Catalog Number YAV14T2

Copper Compression Lug, Heavy Duty, Ring Tongue, 1 Hole w/Inspection Hole, 20-14 AWG, 1/4" Stud, Short Barrel, Tin Plated.



General

Application

For Use On Copper
Commercial (Code) Cable,
Type AN Aircraft Cable And
Extra Flexible Conductors,
Industrials, Hospitals, Electric
Utilities, Shipboard And
Marine, Computers, Steel Mills,
Mining Equipment And Other
Equipment That Is Subject To
Vibration Or Requiring
Dependable Electrical

Performance

Connector Type Ring Terminal

EU RoHS Indicator Yes

Feature - Barrel Style Chamfered
Feature - Barrel Type Standard
Material Copper

Physical Attribute - Number of 1

Holes

Physical Attribute - Tongue Ring

Туре

Plated Y

Plating Type Tin - Electro Plated

Sub BrandHYLUGTrade NameHYLUG™TypeRing TongueUPC781810025321

Dimensions

Dimension - B Length inch 0.25 in
Dimension - Bolt Size fraction 1/4
Dimension - L Length Overall 25 mm

mm

Dimension - Length Overall

inch

Dimension - N inch 0.25 in Dimension - Outside Diameter 0.16 in

inch

Dimension - Pad Width inch 0.42 in Dimension - Stud Size inch 1/4

Dimension - Z inch 0.32 in

Conductor Related

Conductor - Copper Solid Size 20 ;18 AWG;17 AWG;16 AWG;15

AWG;14 AWG

Conductor - Copper Solid Size 20 -14 AWG

Range

Conductor - Copper Str Size 20 AWG;18 AWG;16 AWG;14

AWG

Conductor - Copper Str Size

Range

Conductor Size 16 - 14 AWG

Conductor Type • CU C Solid-Size

• CU C Str-Size

20 AWG - 14 AWG

Certifications and Compliance

Certification - CSA Approved Yes
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Industry Standard(s) UL467
Standards - Industry UL467
Standards Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 1000 Pallet Quantity 99999

Product Assets

Sales Drawings - 50094160

Technical Solutions - BURNDY_YAV14T2_Specsheet



0.99 in