



# YE32P250X125FX, Copper Compression Pin Adapter, 400 kcmil Cu

By Burndy  
Catalog # YE32P250X125FX

Type YE-P copper compression adapters are designed for reliable termination of copper conductor when the current capacity of the conductor is downsized, but larger conductor is utilized. Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used. Accommodates Copper Wire Sizes 400 KCMIL Class B & C, 300 KCMIL Classes G,H,I,K, 313 DLO.



## Application

Typical applications are for voltage drop protection when oversized conductors are used or flex conductor is used

## General

Catalog Number	YE32P250X125FX
Color Code	Blue
Connector Type	INLINE PIN
Construction Material - Main	Copper
Finish Type	Tin-Plated
Material	COPPER
Temperature Rating	90°C
Trade Name	HYPLUG™
Type	Connector
UPC	621945644748

## Electrical Ratings

Voltage Rating	600 V
----------------	-------

## Conductor Related

Conductor - Copper DLO Size	313 KCMIL
Conductor - Copper Flex G Size	300 KCMIL
Conductor - Copper Flex G Size Range	300 KCMIL
Conductor - Copper Flex H Size	300 KCMIL
Conductor - Copper Flex I Size	300 KCMIL
Conductor - Copper Flex K Size	300 KCMIL
Conductor - Copper Str Compact Size	400 KCMIL
Conductor - Copper Str Size	400 KCMIL
Conductor - Material	COPPER
Conductor Size	400 KCMIL
Conductor Type	CODE/FLEX

## Logistics

Carton Quantity	25
Pallet Quantity	3600

## Product Assets

[Catalog Page - BURNDY\\_CopperPinAdapter\\_CatCut](#)  
[Catalogs - Full Line BURNDY Catalog](#)  
[Catalogs - Section C - Compression Connections](#)  
[Sales Drawings - 50119221](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY\_CA-YE32P250X125FX-SPEC-EN | REV 6/2024