



# YTA39R2N, Aluminum Tap Connector, Slotted Tap Pad

By Burndy  
Catalog # [YTA39R2N](#)



AL primary T-tap connector with slotted tap pad designed for easy disconnecting of tap conductor, For use with Types YKA-R-2N and YKA-A-2N, barrel Length: 5.00 IN L.

## General

Catalog Number	YTA39R2N
Connector Type	Tap
Die Index	608
Material	Aluminum
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	N
Type	YTA Series
UPC	781810014004
UPC 12 Digit	7818100140044

## Dimensions

Dimension - B Length inch	5.00 in
Dimension - Bolt Size fraction	1/2
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - Height inch	5.83 in
Dimension - L Length Overall mm	411 mm
Dimension - Length Overall inch	16.19 in
Dimension - Thread Size	1/2

## Conductor Related

Conductor - ACSR Str Size	556.5 (24/7) Parakeet kcmil;556.5 (26/7) Dove kcmil
Conductor - ACSR Str Size Range	556.5 (24/7) Parakeet kcmil-556.5 (26/7) Dove kcmil
Conductor - AL Str Size	636 kcmil;650 kcmil
Conductor - AL Str Size Range	636 kcmil-650 kcmil

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Minimum Pack Quantity	1
-----------------------	---

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Catalogs - Section H - Overhead Distribution](#)  
[Customer Notices - Prop 65 Notice](#)  
[Product Cross Section Image\(s\) - BUR\\_YTA-R-2N\\_LineArt](#)  
[Sales Drawings - SD..051188-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY\_CA-YTA39R2N-SPEC-EN | REV 6/2024