

AGSKIT2, Splice Kit, 8-2 AWG, Heavy Wall Heat Shrink Sleeve, AI/Cu Rated

By Burndy Catalog # AGSKIT2

Splice Kit, 8-2 AWG, w/ Heavy Wall Heat Shrink Sleeve, Al/Cu Rated.



- Dual Rated Aluminum or Copper/Aluminum Combinations
- · Installed with common installation tools
- · Heavy wall heat shrink sleeve is lined with adhesive material providing a positive seal against moisture egress

Application

For All Aluminum or Copper/Aluminum Combinations

General

Catalog Number AGSKIT2

Splice/Heat Shrink Kit Connector Type

EU RoHS Indicator Yes Hex Size Slot Υ Insulation

Material Aluminum Material - Hardware Aluminum Physical Attribute - Screw Type Slot

Plated Plating Type Unplated Sub Brand SPLICE KIT Temperature Rating 194° F

Туре AGSKIT, Above Grade

UPC 781810175293 UPC 12 Digit 7818101752933

Dimensions

Dimension - Height mm $0 \, \text{mm}$ Dimension - L Length Overall 127 mm

Dimension - Length Overall 5 in

inch

Electrical Ratings

Rating - Minimum Voltage 600



Conductor Related

Conductor - AL Str Size 8 AWG;6 AWG;4 AWG;3

AWG;2 AWG

Conductor - AL Str Size Range 8 AWG-2 AWG

Conductor - Copper Solid Size 8 AWG;7 AWG;6 AWG;5

AWG:4 AWG

Conductor - Copper Solid Size 8 AWG-4 AWG

8 AWG;7 AWG;6 AWG;5 Conductor - Copper Str Size

AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Str Size

Range

8-2 AWG Conductor Size

Conductor Type · AL C Str-Size

· CU C Str-Size

8 AWG-2 AWG

Certifications And Compliance

Certification - CSA Approved Yes Certification - ETL No Certification - UL Listed Direct No

Burial

Certification - UL Recognized No Certification - cULus Nο

Industry Standard(s) UL 486A-486B Standards - Industry Standards UL 486A-486B

Standards - RoHS Compliance CM

Status

UL Listed Yes

Product Assets

Catalogs - BURNDY Master Catalog - Section A - Mechanical Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog Product Cross Section Image(s) - BUR_AGSKIT_LineArt

Sales Drawings - SD..211383-01



