

# BIT2/0, Single Sided Two Conductor Clear Insulated Multi-Tap Connector



By Burndy  
Catalog # [BIT2/0](#)

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 14-2/0 AWG, Al/Cu Rated.

## Features

- Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily
- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

## Application

For Indoor Use Only, Copper Or Stranded Aluminum

## General

Catalog Number	BIT2/0
Connector Type	Multi Tap
EU RoHS Indicator	Yes
Hex Key	3/16 in
Installation Torque	120 in-lb
Recommended in-lb	
Insulation	Y
Insulation Type	Plastisol
Material	Aluminum
Material - Hardware	Aluminum
Number Of Ports	2
Physical Attribute - Number of Screws	2
Physical Attribute - Screw Type	Allen
Plated	N
Plating Type	Unplated
Sub Brand	UNITAP
Temperature Rating	90 °C
Trade Name	UNITAP™
Type	BIT
UPC	781810134061
UPC 12 Digit	7818101340611

## Dimensions

Dimension - Height fraction	1.375 in
Dimension - Height inch	1.38 in
Dimension - Height mm	35 mm
Dimension - L Length Overall mm	39 mm
Dimension - Length Overall inch	1.52 in

Dimension - Width fraction	1-2/5 in
Dimension - Width inch	1.4 in
Dimension - Width mm	36 mm

## Electrical Ratings

Operating Voltage	600 V
Voltage - Maximum	600 V

## Conductor Related

Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - AL Str Size Range	14 - 2/0 Str
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Size Range	14 - 2/0 Str
Conductor Size	14-2/0 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• AL C Str-Size</li> <li>• CU C Str-Size</li> </ul>

## Certifications And Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Product Assets

- [3D Models - BIT20\\_MODEL-IGES](#)
- [3D Models - BIT20\\_MODEL-PDF](#)
- [3D Models - BIT20\\_MODEL-STEP](#)

[Catalogs - BURNDY Master Catalog - Section A - Mechanical](#)  
[Catalogs - UNITAP™ Products](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Customer Notices - Prop 65 Notice](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)

[Product Cross Section Image\(s\) - BUR\\_BIT\\_Lineart](#)  
[Sales Drawings - SC210991](#)  
[Specifications - BIT2/0](#)  
[Specifications - Burndy\\_BIT20\\_Specsheet](#)



**A Hubbell brand**

©2024 Hubbell Incorporated. All rights reserved  
BRDY\_MX-BIT20-SPEC-EN | REV 10/2024