

BIT600, Single Sided Two Conductor Clear Insulated Multi-Tap Connector

By Burndy Catalog # BIT600

Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 4 AWG-600 kcmil, Al/Cu Rated.

Features

 Type BIT and BITO (Offset) Multi-tap connectors are installed quickly and easily

Aluminum

- Suitable for use on Code conductor
- UL486B Listed, Dual-rated AL9CU.

Application

For Indoor Use Only, Copper Or Stranded Aluminum

General

Catalog Number BIT600
Connector Type Multi Tap
EU RoHS Indicator Yes
Hex Key 3/16
Insulation Y
Insulation Type Plastisol
Material Aluminum

Number Of Ports 2
Physical Attribute - Number of 2

Screws

Material - Hardware

Physical Attribute - Screw Type Allen Plated N

Plating Type Unplated Sub Brand UNITAP Temperature Rating 90°C Trade Name UNITAP $^{\text{TM}}$ BIT

UPC 781810225257 UPC 12 Digit 7818102252577

Dimensions

Dimension - Height inch 2.75 in

Dimension - Height mm 69.9 mm

Dimension - L Length Overall 69 mm

mm

Dimension - Length Overall 2.72 in

inch



Dimension - Width fraction	2-19/50 in
Dimension - Width inch	2.38 in
Dimension - Width mm	60 mm

Electrical Ratings

Operating Voltage	600 V
Voltage - Maximum	600 V

Conductor Related

Conductor - AL Str Size Range	4 AWG-600 kcmil
Conductor - Copper Str Size	4 AWG-600 kcmil
Range	
Conductor Size	4 AWG-600 KCMIL
Conductor Type	 AL C Str-Size
	 CU C Str-Size

Certifications And Compliance

Certification - CSA Approved	Yes
Certification - UL Listed Direct	No
Burial	
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards	UL 486A-486B
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

Product Assets

3D Models - BIT600_MODEL-PDF
3D Models - BIT600_MODEL-STEP
3D Models - BIT600_MODEL-IGES
Catalogs - BURNDY Master Catalog - Section A - Mechanical
Catalogs - UNITAP™ Products
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice
Interactive Catalog - BURNDY Full-Line Digital Catalog
Product Cross Section Image(s) - BUR_BIT_Lineart
Sales Drawings - SC210991
Specifications - BIT600

