

GAR1529, Mechanical Grounding Connector, Cable to Rod or Pipe

By Burndy Catalog # GAR1529

Mechanical Grounding Connector, Cable to Rod or Pipe, 2/0 AWG (Sol) -250 kcmil, 1" Pipe, 1-1/8"-1-1/4" Rod, #9-#10 Rebar, Bright Dipped.

Features

- Parallel or 90° Copper Cable Connection
- One-wrench installation
- Rated for Direct Burial in earth or concrete

Application

For Joining A Range Of Cable, Parallel Or At Right Angles To Rod Or Tube, Direct Burial Cable, Fence Post

General

Catalog Number	GAR1529
EU RoHS Indicator	Yes
Installation Torque	240 Lb in
Pacammandad Pun in-lh	

Recommended Run in-lb

Installation Torque 240 LBS/in

Recommended in-lb

Material Copper

Material - Hardware DURIUM™ Silicon Bronze

Plated

Plating Type Bright Dipped

Sub Brand MECHANICAL CONNECTOR

1.31 in

GAR Type 244 U Bolt Type

UPC 781810232804 UPC 12 Digit 7818102328044

Dimensions

Dimension - B Length inch	1.75 in
Dimension - Height fraction	3-3/8 in
Dimension - Height inch	3.38 in
Dimension - Height mm	85.9 mm
Dimension - L Length Overall	46 mm
mm	
Dimension - Length Overall	1.81 in

Dimension - Length Overall

Dimension - Outside Diameter

Dimension - Width fraction 2-5/8 in Dimension - Width inch 2.62 in Dimension - Width mm 67 mm

Conductor Related



Conductor - Copper Solid Size	2/0 AWG
Conductor - Copper Solid Size	2/0 AWG-4/0 AWG
Range	
Conductor - Copper Str Size	250 Kcmil
Conductor - Copper Str Size	1/0 -250 kcmil
Range	
Conductor - Copper Tube Std	1 IPS IPS
Size	
Conductor - Copper Tube Std	1 IPS IPS
Size Range	
Conductor - Pipe or Round	1 in
Tube Size Range	
Conductor - Rebar Size	9-10
Conductor - Rebar Size Range	9-10
Conductor - Rod Size	1.120-1.31 in
Conductor - Rod Size Range	1 1/8 in-1 1/4 in
Conductor Type	 CU C Solid-Size
	 CU C Str-Size

• CU Tube Std-Size

Rod-Size

Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct	Yes
Burial	
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards	UL467
Met	
Standards - RoHS Compliance	EX
Status	
ULL isted	Yes

Product Assets

3D Models - GAR1529_MODEL-STEP
3D Models - GAR1529_MODEL-PDF
3D Models - GAR1529_MODEL-IGES
Catalogs - BURNDY Master Catalog - Section E2 - Mechanical
Grounding
Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog
Customer Notices - Prop 65 Notice



©2025 Hubbell Incorporated. All rights reserved BRDY_MX-GAR1529-SPEC-EN | REV 1/2025